

# Heat Outputs

## Fascia Grace Radiators

Type 11

Type 21

Type 22

### Horizontal



Nominal	Length	Single Panel Single Fin	Double Panel Single Fin	Double Panel Double Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$
300mm	600	317		562
	1000	529		937
	1400	741		1312
	2000	1058		1874
400mm	400	272		479
	600	408		719
	800	544		958
	1000	680		1198
	1200	816		1438
	1400	952		1677
	1600	1088		1917
	1800	1224		2156
2000	1360		2396	
500mm	400	329		578
	600	494		866
	800	658		1155
	1000	823		1444
	1200	988		1733
	1400	1152		2022
	1600	1317		2310
	1800	1481		2599
2000	1646		2888	
600mm	400	384	515	670
	600	577	773	1006
	800	769	1030	1341
	1000	961	1288	1676
	1200	1153	1546	2011
	1400	1345	1803	2346
	1600	1538	2061	2682
	1800	1730	2318	3017
	2000	1922	2576	3352
	2300	2210		3855
	2600	2499		4358
3000	2883		5028	

Type 21

Type 22

### Vertical



Nominal	Length	Double Panel Single Fin	Double Panel Double Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$
1800mm	300	886	1046
	450	1329	1569
	600	1772	2092
	750	2215	2615
1950mm	300	936	1103
	450	1405	1654
	600	1873	2205
	750	2341	2756

All heat output are in accordance with BS EN 442 certification.