


Heat Outputs

Fascia Radiators

Horizontal


Type 11 Type 21 Type 22 Type 33



Nominal	Length	Single Panel Single Fin	Double Panel Single Fin	Double Panel Double Fin	Triple Panel Triple Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$
300mm	600	317		562	788
	1000	529		937	1314
	1400	741		1312	1840
	2000	1058		1874	2628
400mm	400	272		479	666
	600	408		719	1000
	800	544		958	1333
	1000	680		1198	1666
	1200	816		1438	1999
	1400	952		1677	2332
	1600	1088		1917	2666
	1800	1224		2156	2999
500mm	400	329	445	578	798
	600	494	668	866	1198
	800	658	890	1155	1597
	1000	823	1113	1444	1996
	1200	988	1336	1733	2395
	1400	1152	1558	2022	2794
	1600	1317	1781	2310	3194
	1800	1481	2003	2599	3593
600mm	400	384	515	670	923
	600	577	773	1006	1384
	800	769	1030	1341	1846
	1000	961	1288	1676	2307
	1200	1153	1546	2011	2768
	1400	1345	1803	2346	3230
	1600	1538	2061	2682	3691
	1800	1730	2318	3017	4153
	2000	1922	2576	3352	4614
	2300	2210	2962	3855	5306
	2600	2499	3349	4358	5998
3000	2883	3864	5028	6921	

Vertical

Type 21 Type 22



Nominal	Length	Double Panel Single Fin	Double Panel Double Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$
1800mm	300	886	1046
	450	1329	1569
	600	1772	2092
	750	2215	2615
1950mm	300	936	1103
	450	1405	1654
	600	1873	2205
	750	2341	2756

All heat output are in accordance with BS EN 442 certification.