

Heat Outputs

Primo Radiators

TYPE 11



TYPE 21



TYPE 22



Nominal	Length	Single Panel Single Fin	Double Panel Single Fin	Double Panel Double Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$
300mm	600	328	478	603
	800	-	-	804
	1000	546	797	1005
	1400	764	1116	1407
	1800	983	1435	1809
	2000	1092	-	2010
400mm	2400	1310	-	2412
	500	356	504	641
	600	427	605	769
	700	498	706	897
	800	569	806	1026
	900	640	907	1154
	1000	711	1008	1282
	1100	782	1109	1410
	1200	853	1210	1538
	1300	924	1310	1667
500mm	1400	995	1411	1795
	1600	1138	1613	2051
	1800	1280	1814	2308
	400	347	484	618
	500	434	605	773
	600	521	725	928
	700	608	846	1082
	800	694	967	1237
	900	781	1088	1391
	1000	868	1209	1546
	1100	955	-	-
	1200	1042	1451	1855
	1300	1128	-	2010
	1400	1215	1693	2164
600mm	1500	1302	-	2319
	1600	1389	1934	2474
	1800	1562	2176	2783
	2000	1736	-	3092
	2400	2083	-	3710
	400	407	560	720
	500	509	700	900
	600	611	840	1079
	700	713	980	1259
	800	814	1120	1439
900	916	1260	1619	
1000	1018	1400	1799	
1100	1120	1540	1979	
1200	1222	1680	2159	
1300	1323	1820	2339	
1400	1425	1960	2519	
1600	1629	2240	2878	
1800	1832	2520	3238	
2000	2036	-	3598	
2400	2240	-	4318	
700mm	400	464	633	817
	500	581	792	1022
	600	697	950	1226
	700	813	1108	1430
	800	929	1266	1634
	900	1045	1425	1839
	1000	1161	1583	2043
	1200	1393	1900	2452
	1400	1625	2216	2860
	1600	1858	2533	3269

All outputs are in accordance with BS EN 442 certification.