

Heat Outputs

Primo Plus Radiators

TYPE 11



TYPE 21



TYPE 22



Nominal	Length	Single Panel Single Fin	Double Panel Single Fin	Double Panel Double Fin
Height	mm	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$
	mm	Watts $\Delta T50$	Watts $\Delta T50$	Watts $\Delta T50$
300mm	600	328	461	580
	800	-	-	773
	1000	546	768	966
	1400	764	1075	1352
	1800	983	1382	1739
	2000	1092	-	1932
	2400	1310	-	2318
400mm	500	356	486	616
	600	427	583	739
	700	498	681	863
	800	569	778	986
	900	640	875	1109
	1000	711	972	1232
	1100	782	1069	1355
	1200	853	1166	1478
	1300	924	1264	1602
	1400	995	1361	1725
	1600	1138	1555	1971
1800	1280	1750	2217	
500mm	400	347	467	594
	500	434	584	742
	600	521	700	891
	700	608	817	1040
	800	694	933	1188
	900	781	1050	1336
	1000	868	1167	1485
	1100	955	-	1634
	1200	1042	1400	1782
	1300	1128	-	1931
	1400	1215	1634	2079
	1500	1302	-	2228
	1600	1389	1867	2376
	1800	1562	2101	2673
2000	1736	-	2970	
2400	2083	-	3564	
600mm	400	407	542	691
	500	509	678	863
	600	611	813	1036
	700	713	948	1209
	800	814	1084	1382
	900	916	1220	1554
	1000	1018	1355	1727
	1100	1120	1491	1900
	1200	1222	1626	2072
	1300	1323	1762	2245
	1400	1425	1897	2418
	1600	1629	2168	2763
	1800	1832	2439	3109
	2000	2036	-	3454
2400	2440	-	4145	
700mm	400	464	615	783
	500	581	768	979
	600	697	922	1175
	700	813	1076	1370
	800	929	1229	1567
	900	1045	1383	1762
	1000	1161	1537	1958
	1200	1393	1844	2350
	1400	1625	2152	2741
	1600	1858	2459	3133

All outputs are in accordance with BS EN 442 certification.